ICS □ 1 3 . 3 1 . 3

3

DB11

..... II
..... III
1 1
2 1
3 1
4 3
5 4
6 5

.....

GB/T1.1-2009

DB11/139-2007

DB11/ 139-2007

2015 5 13

boiler

0.7MW 1t/h

utility boiler

industrial boiler

direct-fired absorption water chiller(heater)

gas-fired heating and hot water combi-boiler

standard condition
273K 101325Pa

O_2 content

continuous emissions monitoring system
/

stack height

new and in-use boiler

high-polluted fuel forbidden area

1 5

1 1

1 5

	2017 3 31	2017 4 1
	5	5
	10	10
	80	30
μ	0.5	0.5

1 1

2 5

	2017 4 1	
	5	10
	10	20
	80	150
μ	0.5	30
	1	1

1 1

1 1 .

1 1

5 水 无 硫

	mg/m^3

	0.2

. 1 粉 迹

SCR 2.5mg/m^3

SNCR 8mg/m^3

. 1 □ 量 系 烧 锅

GB 13271 0.7MW

8m 0.7MW 15m

连 续

1 量 连 续 理 孔 样

DB11/ 1195

1 连 续 平

GB 5468

1 □ 5 连 续

1 □ 1 理

GB/T 16157 HJ/T 397 HJ/T 55

1 □ 1 连 续

4

限 4 连 续

1		GB 5468	HJ/T 76
		GB/T 16157 a	
2		HJ/T 57 HJ 629	
3		HJ/T 42 HJ/T 43 HJ 692 HJ 693 GB 25034 b	
4		HJ 543	-
5		HJ/T 398	-

6		GB/T 15432 HJ/T 55	-
7		HJ 533	-

HJ/T 373

JJG 968

GB/T 16157

1 5

5

		O_2 /%
	*	6
		3
	*	9
		3.5
*		

$$C = C' \times \frac{21-\varphi(O_2)}{21-\varphi'(O_2)} \quad \text{.....}$$

C—— mg/m^3

C’—— mg/m^3

$\varphi(O_2)$—— %

$\varphi'(O_2)$—— %

1μmol/mol 2.05mg/m^3

1μmol/mol 2.86mg/m^3

14MW 20t/h

HJ/T 75 HJ/T 76

式 。

晓 5 3 □ □

限 1 晓 5 3 □ □ 值 阅